

## In the Claims:

1

2

3

10

11

12 13

14

15

16

17

18

19

20

21

22

23

24 25 1. (Currently amended) A folding baby carriage folded so that that comprises four wheels and that is foldable from an unfolded opened state to a folded state whereby the four wheels [[may]] thereof approach each other back and forth and from side to side, further comprising:

a lower frame structure that is positioned over the four wheels to form a seating surface portion of a seat, and folded that is foldable from said opened state to said folded state so as to approach back and forth and from side to side with said four wheels; and

an inverted U-shaped member extending to rise that comprises two upwardly extending bars which extend upward from [[both]] two sides of said seating surface portion, and keeps the same configuration in both opened state and folded state without actually being bent. portion:

wherein said inverted U-shaped member remains on a single plane both in said opened state and in said folded state without being bent out of said plane, said two upwardly extending bars respectively have two upper ends that remain a same distance apart from one another in both said opened state and said folded state, and said two upwardly extending bars respectively have two lower ends that are arranged and adapted to be closer together to one another in said folded state and farther apart from one another in said opened state.

(Currently amended) The folding baby carriage according to claim 1, wherein said inverted U-shaped member <u>further</u> comprises a <u>first and second members middle bar member to which said upper ends of said upwardly extending bars are connected in a state in which a three-dimensional <u>relative</u> movement <u>thereof</u> is restricted.</u>

FASSE PATENT ATTYS

- Currently amended) The folding baby carriage according to claim 2, wherein said [[first]] middle bar member has a respective peripheral wall receiving an edge of said second member a respective one of said upper ends and restricting back-and-forth and up-and-down movements thereof.
- 4. (Currently amended) The folding baby carriage according to
  claim 3, wherein said first and second members are
  connected by further comprising a pin extending in [[the]]
  a back-and-forth direction. direction and connecting said
  middle bar member and a respective one of said upper ends.
- 1 5. (Currently amended) The folding baby carriage according to claim 1, wherein said inverted U-shaped member <u>further</u>
  3. comprises a part of a pair of side vertical bars and a part of an upper end lateral bar connecting <u>together said</u>
  4 upper ends of said <u>upwardly extending bars</u>, and <u>wherein</u>
  5 said upper end lateral bar allows a slight deflection of said upwardly extending bars so that said two lower ends
  7 come closer together in said folded state than in said

13

14

15

16 17

1

2

7

said part of the upper end lateral bar keeps a linear configuration in both opened and folded states, and

said part of the pair of side vertical bars includes upper ends whose distance is not changed in both opened and folded states, and lower ends whose distance is reduced in accordance with transition from the opened state to the folded state.

6. (Currently amended) The folding baby carriage according to claim 5, wherein in [[the]] said opened state, said part of the pair of side vertical bars includes two upwardly extending bars include lower regions extending parallel to each other from [[the]] said lower ends to a predetermined height and upper regions whose distance is reduced toward the upper side. extending upwardly from said predetermined height and slanting closer together toward said upper ends.

## Claim 7 (Canceled).

1 8. (Currently amended) The folding baby carriage according to
2 claim 6, wherein a length of [[the]] a part of [[the]] said
3 upper end lateral bar connecting [[the]] said upper ends of
4 the part of the pair of side vertical said upwardly
5 extending bars is almost the same as a length between outer
6 sides of [[the]] right and left wheels of said four wheels
7 in [[the]] said folded state.

## Claim 9 (Canceled).

3

5

7 8

9

10

11

12

13

5

6

10

1 10. (Currently amended) The folding baby carriage according to claim 9, claim 2, wherein in [[the]] said opened state,

said pair of side vertical bar includes two upwardly extending bars include lower regions extending parallel to each other from [[the]] said lower ends to a predetermined height, upper regions whose distance is reduced toward the upper side, extending upwardly from said predetermined height and slanting closer together toward said upper ends, and horizontal regions extending inward from the upper ends upper portions of said upper regions in [[the]] a width direction and terminating at said upper ends, and

said middle bar <u>member</u> connects [[the]] <u>said</u> inner ends of said <del>pair of</del> horizontal regions.

1 11. (Currently amended) The folding baby carriage according to
2 claim 10, wherein said inverted U-shaped member is a push
3 bar for moving the baby carriage,

said each side vertical bar inverted U-shaped member further includes [[a]] cover member members covering [[a]] respective bar portion portions extending from said horizontal region regions to said upper region, regions, and

said cover member has a projection members respectively have projections protruding outward.



- (Currently amended) The folding baby carriage according to 1 12. 2 claim 11, wherein a distance between <del>a pair of</del> said projections positioned at right and left sides is almost 3 the same as a length between [[the]] outer sides of [[the]] right and left wheels of said four wheels in the folded 5 state. 6
- (Currently amended) The folding baby carriage according to 13. 1 2 claim 5, wherein said lower frame structure has a connection structure [[which]] that is connected to said 3 lower ends and that allows inclination of each part of the 4 5 side vertical bar of said inverted U shaped member said upwardly extending bars in 6 accordance with [[the]] 7 a transition from [[the]] said opened state to [[the]] said 8 folded state.
- (Currently amended) The folding baby carriage according to 1 14. 2 claim 5, wherein said lower frame structure comprises:

a pair of handrail members positioned above [[both]] two sides of the seating surface portion, and

a connection axis turnably connecting a rear end of a respective one of said handrail member members and the part of the side vertical bar of said inverted U-shaped part, a respective one of said upwardly extending bars, and a wall surface of wherein said handrail member includes an abutting wall surface opposed to said side

vertical bar part respective upwardly extending bar through

said connection axis includes an axis, said abutting wall

4631/WFF:ks

3

6 -

7

8

9

10

11

12

surface passing said connection axis and abutting on said
side vertical bar part, respective upwardly extending bar,
and separated wall surfaces positioned above and below
[[the]] said abutting wall surface and forming a clearance
with said <del>side vertical bar part.</del> respective upwardly
extending bar.

- 15. (Currently amended) The folding baby carriage according to claim 5, wherein said lower frame structure comprises:
  - a rear leg having a rear wheel; wheel of said four wheels;

an inverting member turnably connected to said rear leg through a connection pin, provided along said rear leg above said connection pin in [[an]] said opened state, and provided along said rear leg below said connection pin in [[a]] said folded state; and

a connection axis turnably connecting an edge of said inverting member and the side vertical bar part of said inverted U-shaped part, a respective one of said upwardly extending bars, and

includes an abutting wall surface opposed to said side vertical bar part respective upwardly extending bar through said connection axis includes an axis, said abutting wall surface passing said connection axis and abutting on said side vertical bar part, respective upwardly extending bar, and separated wall surfaces positioned above and below [[the]] said abutting wall surface and forming a clearance

8

10

11

- with said side vertical bar part. respective upwardly extending bar.
- 1 16. (Currently amended) The folding baby carriage according to claim 1, wherein said lower frame structure comprises a pair of seating surface supporting side bars extending in [[the]] a back-and-forth direction along [[both]] two sides of [[a]] said seating surface portion in order to support [[the]] a seating surface member from beneath,

wherein [[said]] each one of said seating surface supporting side [[bar]] bars integrally has an inward extending portion extending toward [[the]] an inside so as to support [[the]] said seating surface member from beneath.

- 1 17. (Original) The folding baby carriage according to claim 16,
  wherein said inward extending portion extends from a rear
  part of said seating surface supporting side bar to the
  inside.
- 18. (Currently amended) The folding baby carriage according to claim 16, wherein said inward extending portion is formed by bending a rear end portion of said seating surface supporting side bar to the inside in [[the]] a shape of a horseshoe.
- 1 19. (Currently amended) The folding baby carriage according to claim 16, comprising

3	wherein	said s	eating	surface	member	compr	ises	a
4	plate-shaped	seating	surface	e <del>core</del>	forming	the	seati	ng
5	surface, core							

wherein said seating surface core is connected to said

pair of seating surface supporting side bars.

- 20. (Currently amended) The folding baby carriage according to claim 16, claim 19, wherein said seating surface core is connected to [[the]] said inward extending portions of said pair of seating surface supporting side bars.
- 21. (Currently amended) The folding baby carriage according to
  claim 16, claim 19, further comprising a bending link
  member connecting front portions of said pair of seating
  surface supporting side bars,

wherein said bending link member has a center link bar and a pair of side link bars provided so as to be allowed to be bent, and

said seating surface core is connected to said center link bar.

- 1 22. (Currently amended) A folding baby carriage comprising a
  2 lower frame structure positioned over four wheels to form
  3 a seating surface portion of a seat, in which [[the]] said
  4 lower frame structure is folded; foldable from an unfolded
  5 opened state to a folded state, and further comprising:
- a push bar for moving [[the]] said baby carriage; and

8

9

10

11

12

13

14 15

16

17

18

. 19

20

21

an inverted U-shaped member extending to rise that is separate from said pushbar, and that comprises two upwardly extending bars which extend upward from [[both]] two sides of said seating surface portion; portion and keeping the same configuration in both opened and folded states without actually being bent, separately from said push bar.

wherein said inverted U-shaped member remains on a single plane both in said opened state and in said folded state without being bent out of said plane, said two upwardly extending bars respectively have two upper ends that remain a same distance apart from one another in both said opened state and said folded state, and said two upwardly extending bars respectively have two lower ends that are arranged and adapted to be closer together to one another in said folded state and farther apart from one another in said opened state.

- 1 23. (Original) The folding baby carriage according to claim 22,
  2 wherein said push bar is provided so as to be changeable
  3 between a state pushed from behind and a state pushed
  4 face-to-face.
- 1 24. (Currently amended) The folding baby carriage according to
  2 claim 22, wherein said lower frame structure includes a
  3 pair of handrail members positioned above [[both]] two
  4 sides of [[the]] said seating surface portion, and
  5 said inverted U-shaped member extends to rise upward
  6 from a rear end of said pair of handrail members.

continue we there were the

- (Currently amended) The folding baby carriage according to claim 22, wherein said inverted U-shaped member is used as a frame for supporting a backrest portion of [[the]] said seat.
- 1 26. (Currently amended) The folding baby carriage according to
  2 claim 22, wherein said inverted U-shaped member is used as
  3 a part of a roof for shade.

## [RESPONSE CONTINUES ON NEXT PAGE]